ARMY RESEARCH LABORATORY

Hydrodynamic Breech Window Design Concept for Laser Ignition of Large-Caliber Guns

Stephen L. Howard
Lang-Mann Chang
John Grosh

ARL-TR-1094   June 1996

19960718 080

DTIC QUALITY INSPECTED 3

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY *(Leave blank)*	2. REPORT DATE June 1996	3. REPORT TYPE AND DATES COVERED Final Oct 94 - Sept 95

4. TITLE AND SUBTITLE	5. FUNDING NUMBERS
Hydrodynamic Breech Window Design Concept for Laser Ignition of Large-Caliber Guns	PR: 1L161102AH43

6. AUTHOR(S)

Stephen L. Howard,* Lang-Mann Chang,* and John Grosh**

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER
U. S. Army Research Laboratory ATTN: AMSRL-WT-PA* ATTN: AMSRL-CI-AC** Aberdeen Proving Ground, MD 21055-5066	ARL-TR-1094

9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)	10.SPONSORING/MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT	12b. DISTRIBUTION CODE
Approved for public release; distribution is unlimited.	

13. ABSTRACT *(Maximum 200 words)*

Laser ignition is becoming a viable method of igniting a propellant bed (especially for large-caliber guns). However, problems still are present at the optical interface of the laser and the round to be fired. The most obvious problem to the casual observer is the deposits left on the window from the ignition of the igniter material and propellant. If the window is obscured (by an opaque coating or by opaque particles), ignition of subsequent rounds may not be possible. Therefore, a method of keeping the window clean for an extended number of firings is needed. Instead of physically wiping the window after each firing, this study examined the use of hydrodynamic flow of the igniter gases to keep the obscuring particles and hot gases from making contact with the window. Initial experiments used visualization by water jets to validate theoretical predictions for deflecting the particle-laden fluid flow. Improvements to the basic design included a cyclonic chamber in the window region to remove particles. Predictions indicated that the maximum pressure in the cyclonic chamber would be about 75% of the maximum breech pressure. Designs were tested in both subscale (76-mm I.D.) and full-scale (155-mm I.D.) simulators made of optically clear polymer resins. Several of these designs dramatically reduced the amount of particles that reached the window area.

14. SUBJECT TERMS		15. NUMBER OF PAGES
Ignition Studies; Primers; Flamespreading; Gun Simulator; Laser Ignition		36
		16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	SAR

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

INTENTIONALLY LEFT BLANK.

1.   INTRODUCTION

The laser ignition concept for initiating large-caliber ammunition was originally conceived and tested at the U.S. Ballistic Research Laboratory* at Aberdeen Proving Ground, MD 21005-5066 (Robitalle 1964; Barrows et al. 1993). The ability to ignite propellant beds by using laser radiation as the ignition source should eliminate the need for primers and simplify the ignition train of ammunition as well as improve the safety of the firing procedure.

However, if the laser radiation cannot reach the igniter material that subsequently ignites the propellant, the propellant cannot ignite. Important to all schemes that transmit laser radiation into the breech of a gun is an optical window. This window must be made of a material that transmits the laser radiation without deleterious effects to the material and must withstand the high-temperature, high-pressure, and chemically hostile environment of the breech during the ballistic cycle. In addition, the window material and/or design must eschew particles created during the ballistic cycle that would otherwise be deposited on the window. If particles remain on the window surface, the laser radiation transmission will be reduced for the subsequent firing (see Figure 1). At some point, if the window were not sufficiently cleaned, it would no longer transmit, and further firing would be impossible. Also, if thermal shock from contact with the hot gases were to occur, the window would crack and the pressure seal would be lost.

---

* On 30 September 1992, the U.S. Army Ballistic Research Laboratory (BRL) was deactivated and subsequently became part of the U.S. Army Research Laboratory (ARL) on 1 October 1992.

Figure 1. Effect of dirty window on laser ignition.

A cleaning procedure that required swabbing the window after each firing would
not be acceptable for many reasons, the least of which is the requirement for rapid firing.
Cleaning with a brush mounted on the breech should meet with only partial success. The
brush would rapidly become contaminated and in a steady-state condition would leave
particles on the window as it brushes others away. Therefore, a breech brush would
require frequent replacement in order to avoid the steady-state condition.

A cleaning procedure that would work with only a subset of the ammunition (those
that require a stub base) would be a double window. If a window were mounted in the
stub base as well as in the breech, the stub base window should provide an optically clean
screen for the breech window that would be thrown away with every round. Such a
procedure would dramatically increase the cost of ammunition since acceptable windows
are not inexpensive. This paper presents a change in paradigm from the aforementioned
methods. A technique that uses the gases from propellant combustion to keep the window
clean is discussed. Hydrodynamic forces will always be present in a gun as long as

propellant and hot, high-pressure gases are used to propel the projectile. If a cavity is placed in the spindle, these forces can be utilized to keep the window clean.

2. CALCULATION OF PRESSURE IN THE CAVITY

Figure 2 schematically represents the flow system composed of the cavity in the spindle and the gun chamber. The two flow volumes are connected by two orifices of equal diameter. During the early phase of the interior ballistic cycle, the pressure in the gun chamber rises following the combustion of the propelling charge. A flow of propellant gases to the cavity through the orifice then occurs. At some point in the ballistic cycle after the gun chamber pressure has reached its peak value, the pressure in the cavity becomes higher than that in the gun chamber. The flow reverses its direction until the end of the interior ballistic cycle.


Figure 2. <u>Proposed flow system for hydrodynamic cleaning of window</u>.

Since the gas flow through the orifice is a flow with high Reynolds numbers, it is appropriate to consider the flow as a one-dimensional, inviscid flow system for the primary interest of predicting the pressure rise in the cavity. The following sections contain the governing equations for the flow system.

3

2.1 Equation of State. The Nobel-Abel equation of state is adopted and written as:

$$P_c = \frac{R_u \, T_c \, W}{V_c \, m \, - \, b \, W} \, ,$$ (1)

where P_c, T_c, W, and V_c are the pressure, temperature, total mass, and volume of the cavity, respectively. Furthermore, m, b, and R_u are the molecular weight, covolume, and universal gas constant of the propellant gases, respectively.

2.2 Continuity Equations. It is noted that there are two modes, choked and nonchoked, of flow through the orifice during the interior ballistic cycle. A choked flow occurs when

$$\frac{P^*}{P_o} = [\frac{2}{k+1}]^{k/(k-1)} \, ,$$ (2)

where $P^* =$ pressure of expanding fluid at which a choked flow occurs, P_o, T_o equal the pressure and temperature in gun chamber, and $k =$ ratio of specific heats. For propellant gases, $k = 1.243$, and the pressure ratio in equation (2) is calculated to be 0.556. In the equation, P_o can be obtained from calculations using XKTC code or others (Gough 1986).

2.2.1 Flow From the Gun Chamber to the Cavity. When $\frac{P_c}{P_o} \leq 0.556$ (choked flow): The flow rate through the orifice is (Shapiro 1953)

$$\dot{\omega} = C_d A \frac{P_o}{\sqrt{T_o}} \sqrt{\frac{kg}{R_u} [\frac{2}{k+1}]^{(k+1)/(k-1)}} \, ,$$ (3)

where $C_d =$ discharge coefficient of orifice, $A =$ cross-sectional area of orifice, and $g =$ gravity.

When $\frac{P_c}{P_o} > 0.556$ (nonchoked flow): The flow rate is

$$\dot{\omega} = C_d A \sqrt{\frac{kg}{R_u}} \frac{P_c}{\sqrt{T_o}} M \sqrt{1 + \frac{k-1}{2} M^2} \, ,$$ (4)

where $M =$ Mach number given as

$$M = \sqrt{\frac{2}{k-1} [(\frac{P_o}{P_c})^{(k-1)/k} - 1]} \, .$$ (5)

4

2.2.2 Flow from the Cavity to the Gun Chamber. When $\frac{P_o}{P_c} \leq 0.556$ (choked flow): The flow rate is

$$\dot{\omega} = -C_d A \frac{P_c}{\sqrt{T_c}} \sqrt{\frac{kg}{R_u} \left[\frac{2}{k+1}\right]^{(k+1)/(k-1)}} \qquad . \tag{6}$$

When $\frac{P_o}{P_c} > 0.556$ (nonchoked flow): The flow rate is

$$\dot{\omega} = -C_d A \sqrt{\frac{kg}{R_u}} \frac{P_o}{\sqrt{T_c}} M \sqrt{1 + \frac{k-1}{2} M^2} \tag{7}$$

with

$$M = \sqrt{\frac{2}{k-1} \left[\left(\frac{P_c}{P_o}\right)^{(k-1)/k} - 1\right]} \qquad . \tag{8}$$

2.3 Energy Equations.

2.3.1 Flow From the Gun Chamber to the Cavity. For either a choked or nonchoked flow, the rate of temperature change in the cavity is

$$\dot{T}_c = \frac{\dot{\omega}}{W C_v} [(1-\phi) C_p T_o - C_v T_c] \qquad , \tag{9}$$

where ϕ = heat loss to the walls of the cavity, including the orifice area; C_p = constant pressure specific heat; and C_v = constant volume specific heat.

2.3.2 Flow From the Cavity to the Gun Chamber.

$$\dot{T}_c = \frac{\dot{\omega} T_c}{W C_v} (C_p - C_v) \qquad . \tag{10}$$

5

3. EXPERIMENTAL

3.1 <u>Water Jet Simulator.</u> Initial visualizing of the diverted jet concept was performed using water. Figure 3 shows a water tank with provisions for pressurized water addition as well as a removable bottom plate that contained the jet orifices. Plates were tried with angles of 30°, 45°, and 60° (see Figure 2) between the jets. The larger angles required a two-stage structure for the diverting jet orifice. Otherwise, at large angles the entrance to the diverting jet would be too far from the direct jet. Therefore, a large entrance was drilled part way through the plate and was parallel to the direct jet. The diverting jet was then drilled so as to intersect the entrance hole and the exit of the direct jet

Figure 3. <u>Schematic of water jet visualization system.</u>

(see Figure 2).The tank system was supported by four acrylic tubes over a drainage system. Operation of the system was then videotaped.

3.2 <u>Flamespread Chamber.</u> For subscale tests, the flamespread chamber (Figure 4) was used (Kooker, Chang, and Howard 1992; Kooker, Howard, and Chang 1994). The flamespread chamber consisted of a transparent acrylic tube (interior diameter of 76 mm with an axial dimension of 305 mm) contained in a steel confinement casing. Ports were machined in the steel casing and the acrylic tube for pressure transducers.

6

Figure 4. Cross-sectional view of flamespread simulator with cavity and igniter chambers.

For these experiments, the acrylic tube was split into two regions (igniter and breech window regions). The igniter region of the tube was closest to the right side of the simulator and contained a cloth basepad (containing black powder, ball powder, or clean burning [CBI] material). The basepad was ignited by a low-shock igniter located on the outside of the basepad facing the breech region so that laser ignition could be modeled (see Figure 4). A pressure transducer was located in each chamber. Other pressure transducers were located in various parts of the chamber, simulating the laser breech window area. The low-shock igniter was electrically connected to the firing line via a high-pressure electrical feedthrough in the top of the simulator. The chamber was also placed on the horizontal to approximate typical tank or artillery use.

The window region was experimentally modelled by a 4.25-mm O.D. aluminum plug (a threaded right-circular cylinder) that was highly polished on one end to form a witness plate and slotted on the other end so that it could be screwed out of the hollow tube for viewing (the hollow tube was made of aluminum and was internally threaded at the window region so that it could tightly hold the witness plate in place). The plug was chosen so that a leak-proof seal could be maintained in the window region and yet allow

7

easy access to the witness plate for evidence of residues from the igniter material combustion.

3.3 Full-Scale Simulator. The full-scale simulator was a 165-mm interior diameter by 1,000-mm-long acrylic tube with aluminum end plates held in place by four threaded rods (see Figure 5). The igniter chamber was scaled up from the subscale simulator chamber. The conical cavity chamber was cast in the bottom of the acrylic tube with an aluminum cover plate that contained the jet orifices and isolated the cavity from the main chamber that contained the basepad. The casting material was a pourable polystyrene-polyester mix that was transparent upon solidification. Operation of the full-scale simulator was identical to that of the subscale simulator.

Figure 5. Schematic of full-scale simulator.

4. RESULTS AND DISCUSSION

4.1 Calculations. The governing equations described previously can be integrated numerically using a conventional integration method (see Appendix). The input data for the computer program are:

8

Discharge coefficient of orifice $C_d = 0.62$
Cross-sectional area of the orifice $A = 0.0000565$ m^2
Ratio of specific heats, $k = 1.243$
Volume of cavity, $V_c = 0.0000872$ m^3 and 0.000127 m^3
Specific covolume, $b = 0.00103$ m^3/kg
Molecular weight, $m = 23.4$ kg/kg-mole
Constant volume specific heat, $C_v = 456$ J/K-kg
Constant pressure specific heat, $C_p = 566$ J/K-kg
Gravitational acceleration, $g = 9.81$ m/s^2
Conversion factor, $J = 778$
Universal gas constant, $R_u = 8314$ J/K kg-mole
Initial pressure in the cavity, $P_{co} = 0.101$ MPa
Initial temperature in the cavity, $T_{co} = 295$ K
Heat loss to the cavity walls, $\phi = 0.1$ and 0.2 .

Note that the cross-sectional area, A, given here is the combined cross-sectional area of the two orifices in the window design, each with a diameter of 4.25 mm (0.165 inch). This diameter is sufficient for a laser beam to pass through. It is possible to open a cavity inside the spindle with a volume, V_c, ranging from 0.0000872 to 0.000127 m^3 without causing a structural failure of the spindle upon high-pressure loadings during the ballistic cycle. As for heat loss to the cavity walls, ϕ is difficult to accurately determine without conducting a complex three-dimensional flow analysis. However, from experience gained from closed bomb testing of propellants, it is reasonable to assume the heat loss to be in the range of 10 to 20% of the total energy entering the two orifices. In a continuous firing series, the heat loss will decrease accordingly.

A smaller V_c will result in a higher pressure rise in the cavity. Figure 6 presents calculated pressure rises in the cavity with $V_c = 0.000127$ m^3 corresponding to two assumptions of heat loss. During the interior ballistic cycle, the maximum pressure differentials between the gun chamber and the cavity, $\Delta P = P_o - P_c$, are 180 MPa and 200 MPa for $\phi = 0.10$ and $\phi = 0.20$, respectively. Based on the larger value of these two pressure differentials, the shear stress, S, across the solid between the gun chamber and the cavity is calculated by Equation 11.

$$ S = \frac{\Delta P \; A_1}{A_2} \; , \tag{11} $$

where A_1 is the surface area on which the pressure, ΔP, applies and A_2 is the cross-sectional area across the solid. The values of A_1 and A_2 for the proposed cavity are

9

0.00310 m^2 and 0.00501 m^2, respectively. The resulting maximum shear stress on the interface between the gun chamber and the cavity chamber is 124 MPa.

Figure 6. Pressure and Δp curves of gun chamber and cavity chamber with heat losses of 10% and 20%.

4.2 Water Jets. The water tank was connected to the domestic water supply at a pressure of approximately 0.3 MPa (40 psig). The tank was vented and the water flow from the exit orifices observed. The flow was diverted at an angle from the direct jet orifice (see also Figures 2 and 3). The diverting angle was slightly less than half the angle of the diverting jet. This result was expected. At a diverting jet angle of 60°, the diverted distance was greatest for the angles tested. The water jet appeared to completely miss the region where the window would be placed (see the object under the jets in Figure 3). The angle of 60° was the largest angle possible for the machining techniques utilized. Therefore, this angle was chosen for further study in the simulators.

4.3 Flamespread Chamber (Subscale Simulator). The first tests with the subscale simulator used a simple chamber (a right-circular cylinder) for the cavity (see Figure 4). A baseline test with Class 3 black powder was run with only a direct jet (e. g., the diverting jet was not completely drilled) and without the cavity tube shown in Figure 4.

10

The black powder residue particles were captured on a mylar sheet placed over the window orifice. Comparison of the before and after photographs in Figure 7 of the orifice entrances showed that black powder residue in the gun chamber portion of the simulator is indeed very dirty. As shown in Figure 8, the number of particles that passed through the direct jet was quite large. It is doubtful that a laser beam penetrating this residue layer (without first a cleaning procedure) could successfully ignite an igniter pad.

(a)   (b)

Figure 7. Before (a) and after (b) photographs of orifice entrances.

Figure 8. Black powder residue particles collected at window in baseline test.

11

In addition to not directly hitting the window region by the opening of the diverting jet for the remainder of the tests, the igniter gases were prevented from directly contacting the window witness plate by placing a hollow tube of 4.25-mm I.D. tube that extended from the window witness plate to nearly the exit of the orifices that form the jets (see Figures 2 and 4). It was thought that the initial air in the tube would act as a "buffer" that would compress as igniter gases entered the cavity chamber, thereby preventing a direct path to the window for both particles and hot gases. These tests also used Class 3 black powder in the basepad.

This particular technique drastically reduced the particles that attached to the window region. However, protection of the window was not particularly successful. A slight film and a large number of particles still covered the window witness plate (see Figure 9b). Fortunately, it was noted that the majority of particles in the diverted gas flow hit the chamber wall and then appeared to flow back toward the front of the cavity. It was posited that this recirculating flow carried the particles that finally attached to the window. Borrowing technology commercially available for separating particles from gas flows, the cavity chamber was changed from a right-circular cylinder to a tapered cone with the minimum diameter in the window region. This shape formed a hydrocyclone (see Figure 10a) that would separate particles from a tangential gas flow. While the diverted flow into the cavity chamber is not purely tangential, the flow becomes largely tangential upon impacting the curved wall of the cone. The tangential velocity component increases if the diverting jets are offset from the center of the cone. Fortunately, such is the case for the breech spindle currently in use for 155-mm cannon—the primer hole is offset by 14 mm to accommodate such features as the Swedish notch.

(a)

(b)

Figure 9. Before (a) and after (b) photographs of window witness plate.

(a)

(b)

Figure 10. Hydrocyclone chamber (a) and window witness plate (b).

This technique reduced to single digits the number of particles that finally found the window (see Figure 10b). When clean-burning igniter (CBI) material instead of black powder was used, particles were not noticed on the window witness plate. It was decided that black powder represented the worst case. An experiment was then tried with ten consecutive shots of black powder before examining the witness plate. The witness plate had few particles and was only slightly filmed. A larger number of shots would have been

needed before laser light would begin to be seriously attenuated. Fortunately, at low rates of loading of the window the laser can burn off some of the contaminates as it ignites successive shots, thereby increasing the total number of shots before cleaning of the window.

4.4 Full-Scale Simulator. The full-scale simulator was made to resemble the end of the breech chamber and the spindle face in a 155-mm cannon. The simulator utilizing the conical cavity chamber showed no deviation from the results of the subscale simulator. As evidenced by residue particles that attached themselves to the wall of the conical chamber, the gas flow from the diverting jet avoided the window region and appeared to move in a circular path in the cavity chamber. The window region remained essentially clean (similar to the witness plate in Figure 10b) while using black powder as the igniter material.

5.   SUMMARY

Both liquid- and gas-phase jets exiting from a pressurized chamber into a second gas-filled chamber of lower pressure can be diverted from the line-of-sight through the jet orifices. This concept was used in a 155-mm cannon simulator to reduce the dirt and thermal shock that can affect the window used for laser ignition. Gases emanating from an igniting basepad that would otherwise impinge upon and obscure the window were diverted. The gases were further processed by centrifugal force within a conical cavity next to the window to remove solid particles from the gas flow that could otherwise attach to the window. An air buffer zone just above the window was also provided. These two techniques kept hot, dirty gases from the window. They should be effective in protecting the window from thermal shock and from becoming dirty, which would block the laser beam required to ignite the basepad.

6. REFERENCES

Barrows, A. W., B. E. Forch, R. A. Beyer, A. Cohen, and J. E. Newberry. "Laser Ignition in Guns, Howitzers and Tanks: The Light Program." ARL-TR-62, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, February 1993.

Gough, P. S. "The XNOVAKTC Code." PGA-TR-86-1, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, March 1986.

Kooker, D. E., L.-M. Chang, and S. L. Howard. "An Attempt to Characterize Planar Flamespreading in Granular Propellant: Preliminary Results." 29th JANNAF Combustion Meeting, CPIA Publication 593, vol. I, p. 1, 1992.

Kooker, D. E., S. L. Howard, and L.-M. Chang. "Flamespreading in Granular Solid Propellant: Initial Results." ARL-TR-446, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, June 1994.

Robitalle, L. L. "Laser-Induced Initiation of Military-Type Solid Propellants," BRL-MR-1549, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 1964.

Shapiro, A. H. The Dynamics and Thermodynamics of Compressible Fluid Flow. New York: Ronald Press Co., 1953.

APPENDIX:

FORTRAN PROGRAM CODE

INTENTIONALLY LEFT BLANK.

There are three files:

```
source.f      = source code listing
data.inc      = include file
constants.inc = include file      .
```

"Include" files are pieces of code which get inserted into the program at compilation. Constants and common block information were placed into these files.

To compile the code, SLATEC libraries must be installed on the system.

f77 -o chamber source.f /usr/lib/slatec/lib/slatec.a

The SLATEC (acronym for Sandia, Los Alamos, Air Force Weapons Laboratory Technical Exchange Committee) mathematic libraries perform a wide variety of functions such as solving linear systems of equations, ordinary and partial differential equations, spline interpolation, etc. This FORTRAN library is in the public domain and can be obtained from the following organization:

```
Energy Science and Technology Software Center
P.O. Box 1020
Oak Ridge, TN  37831
Telephone  615-576-2606
E-mail: estsc%a1.adonis.mrouter@zeus.osti.gov          .
```

The following codes were compiled on an Silicon Graphics Indigo. Silicon Graphics Inc. freely distributes the SLATEC libraries for their workstations and file servers.

===
        Filename: source.f

===
        PROGRAM CHAMBER

C--
C State Variables:
C
C PC = chamber pressure (psi)
C TC = chamber temperature (R)
C W   = mass in chamber (lb)
C Tdot = time derivative of temperature (R/s) in chamber
C Wdot = time derivative of mass (lb/s) in chamber

```
C----------------------------------------------------------------
C  Time-dependant parameters:
C
C  P0 = gun chamber pressure (psi)  - from XKTC lookup table
C  T0 = gun chamber temperature (R) - from XKTC lookup table
C----------------------------------------------------------------
C  Initial Conditions:
C
C  PC0   = initial chamber pressure (lbf/ft^2)
C  TC0   = initial chamber temperature (R)
C  W0    = initial mass in chamber (R)
C  time0 = start time (ms)
C  timef = end time (ms)
C----------------------------------------------------------------

       IMPLICIT DOUBLE PRECISION (A-H,O-Z)
       DOUBLE PRECISION K,M

       EXTERNAL DDASSL
       EXTERNAL RES,EOSW,DYNAM

       INTEGER NEQ,NG,MAXORD,LIW,LRW

       PARAMETER(N     = 15)
       PARAMETER(NEQ   = 3)
       PARAMETER(MAXORD = 5)
       PARAMETER(LIW   = 20+NEQ)
       PARAMETER(LRW   = 40+(MAXORD+4)*NEQ+NEQ**2)

       INTEGER INFO(N), IDID, IWORK(LIW), IPAR

       DOUBLE PRECISION TIME, TIME0,TIMEF, TIMEOUT,
      &          Y(NEQ), YPRIME(NEQ),
      &          RTOL, ATOL,RWORK(LRW), RPAR

       LOGICAL IFLAG
```

```fortran
      SAVE JLO

c     Common blocks for input data.

#include "data.inc"

      CALL GETDATA()

      PC0 = PRESX(1)
      TC0 = TEMPX(1)
      CALL EOSW(PC0,TC0,W0)

      TIME0 = TIMEX(1)
      TIMEF = TIMEX(NDATA)
      NPTS  = 1000
      DTIME = (TIMEF-TIME0)/(NPTS)

      RTOL = 1.0D-06
      ATOL = 0.0D0

      CALL DYNAM(YPRIME(1),YPRIME(2),TIME0,PC0,TC0,W0)

      YPRIME(3) = 0.0D0

c     set initial conditions

      Y(1) = W0
      Y(2) = TC0
      Y(3) = PC0

      CALL SETINFO(INFO)

      TIME    = TIME0
      TIMEOUT = TIME + DTIME

      CALL OUT(TIME,TIMEOUT,Y,YPRIME,TC0,PC0)
```

```fortran
      DO 100 I = 1, NPTS-1
          CALL DDASSL (RES, NEQ, TIME, Y, YPRIME, TIMEOUT,INFO,
     &              RTOL, ATOL, IDID, RWORK, LRW, IWORK,
     &              LIW, RPAR, IPAR, JAC)
          CALL INTERP(TIMEX,TEMPX,PRESX,NDATA,TIME,T0,P0)
          CALL OUT(TIME,TIMEOUT,Y,YPRIME,T0,P0)

          TIME   = TIMEOUT
          TIMEOUT = TIME + DTIME
100   CONTINUE

      END


c     -----------------------------------------------------------------
      SUBROUTINE SETINFO(INFO)

c     Purpose: initialize information array

      INTEGER INFO(15)
      DO 100 I = 1, 15
         INFO(I) = 0
100   CONTINUE

      END


c     -----------------------------------------------------------------
      SUBROUTINE OUT(T,TOUT,Y,YPRIME,T0,P0)

c     Purpose: print out results

      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      DOUBLE PRECISION Y(*),YPRIME(*),PHAT

      PHAT = P0/Y(3)
      WRITE(6,'(11E20.10)') T,Y(3)/144.0D0,Y(2),Y(1),T0,P0/144.0,
```

```fortran
      &           PHAT,YPRIME(1),YPRIME(2),YPRIME(3),1.0D0/PHAT

      END



      SUBROUTINE GETDATA()

c    Purpose: read in input data

      CHARACTER*80 FILENAME

#include "data.inc"

      READ(*,*) FILENAME
      READ(*,*) FLOSS
      READ(*,*) Vc
      READ(*,*) A
      READ(*,*) Cd

       OPEN(20,FILE='xktc.data')
      REWIND(20)
      DO 100 I = 1, NMAX
        READ(20,*,END=200) TIMEX(I), PRESX(I), TEMPX(I)

c       convert pressure from psi to lb/ft^2
        PRESX(I) = 144.0 * PRESX(I)
100   CONTINUE

200   NDATA = I - 1

      END
      SUBROUTINE RES(T,Y,YPRIME,DELTA,IRES,RPAR,IPAR)

      DOUBLE PRECISION Y(*),YPRIME(*),DELTA(*)
      DOUBLE PRECISION P0,T0,TC,PC,W,WDOT,PDOT,TDOT
```

```fortran
      EXTERNAL EOSP, DYNAM

      W  = Y(1)
      TC = Y(2)
      PC = Y(3)

c     compute dynamic variables

      CALL DYNAM(WDOT,TDOT,T,PC,TC,W)

c     compute pressure from equation of state

      CALL EOSP(PC,TC,W)

      DELTA(1) = YPRIME(1) - WDOT
      DELTA(2) = YPRIME(2) - TDOT
      DELTA(3) = Y(3) - PC

      END



      SUBROUTINE DYNAM(WDOT,TDOT,TIME,PC,TC,W)

c     Describe dynamic equations for system

      DOUBLE PRECISION P0,T0,TC,PC,W
      DOUBLE PRECISION WDOT,PDOT,TDOT,PHAT,TIME,M

c     common black for input data

#include "data.inc"
#include "constants.inc"

C     Obtain gun chamber pressure and temperature from lookup table:

      CALL INTERP(TIMEX,PRESX,TEMPX,NDATA,TIME,P0,T0)
```

```fortran
C   Compute time derivative of mass in chamber.  Note that
C     PHAT < 0.556 implies choked flow. For P_gun > PC,

      IF (P0 .GE. PC) THEN
        PHAT = PC/P0
        IF (PHAT .GT. 0.556D0) THEN
          M = dsqrt((((-1.0D0 + (1.0D0/PHAT)**((k-1.0D0)/k))
     &           *2.0D0/(k-1.0D0)))


          Wdot = Cd * A * dsqrt(k * g / R) * (PC / dsqrt(T0)) *
     &           M * dsqrt(1.0D0 + 0.5D0 * (k-1.0D0) * M**2)
        ELSE
          Wdot = Cd * A * dsqrt( (k * g / R) *
     &           ((2.0D0/(k+1.0D0))**((k+1.0D0)/(k-1.0D0))))
     &           *P0/dsqrt(T0)
        ENDIF
        Tdot = (Wdot/(W*Cv)) * (Cp*T0*floss - Cv*TC)
      ELSE
        PHAT = P0/PC
        IF (PHAT .GT. 0.556D0) THEN
          M = dsqrt((((-1.0D0 + (1.0D0/PHAT)**((k-1.0D0)/k))
     &           *2.0D0/(k-1.0D0)))


          Wdot = -Cd * A * dsqrt(k * g / R) *
     &           (P0 / dsqrt(TC)) * M * dsqrt(1.0D0+0.5D0*
     &           (k-1.0D0)*M**2)
        ELSE
          Wdot = -Cd * A * dsqrt( (k * g / R)*
     &           ((2.0D0/(k+1.0D0))**((k+1.0D0)/(k-1.0D0))))
     &           *PC/dsqrt(TC)

        ENDIF
        Tdot = (Wdot/(W*Cv)) * TC * (Cp - Cv)
      ENDIF
```

```fortran
      END


      SUBROUTINE EOSP(PC,TC,W)

c     equation of state for computing chamber pressure

      DOUBLE PRECISION PC,TC,W

#include "data.inc"
#include "constants.inc"

      PC = Ru * TC * W / (Vc * MW - b * W)

      END


      SUBROUTINE EOSW(PC,TC,W)

c     equation of state for computing mass inside chamber

      DOUBLE PRECISION PC,TC,W

#include "data.inc"
#include "constants.inc"

      W  = PC * Vc * MW / (PC * b + Ru * TC)

      END

      SUBROUTINE INTERP(T,X,Y,N,TINT,XINT,YINT)
c -----------------------------------------------------------------
c    Linear interpolation from data table.
c
c    Input:
c         T   = ordered array of length N representing the
```

```
c              data domain (must be either monotonically
c              increasing or descreasing).
c       X   = data array of length N.
c       Y   = data value of length N.
c       TINT = interpolation point.
c
c    Output:
c       XINT = interpolated X-value at point TINT
c       YINT = interpolated X-value at point TINT
c --------------------------------------------------------------

       DOUBLE PRECISION T(*),X(*),Y(*),TINT,XINT,YINT
       DOUBLE PRECISION THETA
       SAVE JLO

       CALL HUNT(T,N,TINT,JLO)
       IF (JLO .LE. 0) THEN
         XINT = X(1)
         YINT = Y(1)
       ELSE IF (JLO .GE. N) THEN
         XINT = X(N)
         YINT = Y(N)
       ELSE
         THETA = (TINT - T(JLO))/(T(JLO+1)-T(JLO))
         XINT  = X(JLO) + THETA * (X(JLO+1) - X(JLO))
         YINT  = Y(JLO) + THETA * (Y(JLO+1) - Y(JLO))
       ENDIF

       END


       SUBROUTINE HUNT(XX,N,X,JLO)
c --------------------------------------------------------------
c    Purpose: Search ordered list.
c
c    Source:  This subroutine was copied from the following book:
```

27

```
c
c            W.H. Press, B.P. Flannery, S.A. Teukolsky, W.T. Vetterling
c         Numerical Recipes
c         The Art of Scientific Computing
c         Cambridge University Press, New York, 1986.
c         Pages 91-92.
c
c   Input:
c         xx  = ordered array, must be either monotonically
c              increasing or descreasing
c         n   = length of array XX
c         x   = data value
c         jlo = initial guess for index search
c
c   Output:
c         jlo = index value for xx(jlo) <= x < xx(jlo+1),
c              jlo=0 or jlo=N indicates that x is out of
c              range.
c ----------------------------------------------------------------

      DOUBLE PRECISION XX(N),X
      LOGICAL ASCND
      ASCND = XX(N) .GT. XX(1)

      IF (JLO .LE. 0 .OR. JLO .GT. N) THEN
        JLO = 0
        JHI = N + 1
        GOTO 3
      ENDIF

      INC = 1
      IF (X .GE. XX(JLO) .EQV. ASCND) THEN
1       JHI = JLO + INC
        IF (JHI .GT. N) THEN
          JHI = N + 1
        ELSE IF (X .GE. XX(JHI) .EQV. ASCND) THEN
```

```
          JLO = JHI
          IN = INC + INC
          GOTO 1
        ENDIF
      ELSE
        JHI = JLO
2       JLO = JHI - INC
        IF (JLO .LT. 1) THEN
          JLO = 0
        ELSE IF (X .LT. XX(JLO) .EQV. ASCND) THEN
          JHI = JLO
          INC = INC + INC
          GOTO 2
        ENDIF
      ENDIF
    ENDIF

3   CONTINUE

    IF (JHI - JLO .EQ. 1) RETURN

    JM = (JHI + JLO)/2
    IF (X .GT. XX(JM) .EQV. ASCND) THEN
      JLO = JM
    ELSE
      JHI = JM
    ENDIF

    GOTO 3
    END
```

===
          Filename: data.inc

===
C--
C Design Parameters:
C
```

```
C  Vc   = volume of chamber [ft^3]
C  A    = area of duct [ft^2]
C  Cd   = discharge coefficient
C  floss = fraction heat loss from tube
C
C  TIMEX() = table from XKTC output of time values (ordered)
C  PRESX() = table from XKTC output of gun pressure values (lb/ft^2)
C  TEMPX() = table from XKTC output of gun temperature values (R)
C-----------------------------------------------------------------

      PARAMETER(NMAX  = 5000)
      DOUBLE PRECISION TIMEX(NMAX), PRESX(NMAX), TEMPX(NMAX)
      DOUBLE PRECISION FLOSS,A,Vc,Cd
      INTEGER NDATA

      COMMON /XKTC1/ TIMEX, PRESX, TEMPX
      COMMON /XKTC2/ NDATA
      COMMON /PARAM/ FLOSS,Vc,A,Cd


C-----------------------------------------------------------------
C Original problem:
C
C    floss = 0.85D0
C    Vc    = 0.005787D0
C    A     = 0.000608D0
C    Cd    = 0.62D0
C-----------------------------------------------------------------


===============================================================
          Filename: constants.inc

===============================================================
C-----------------------------------------------------------------
C  Constants:
C
C  R  = gas constant [ft-lb/(lb R)]
C  MW = molecular weight [lb/lb-mole]
```

```
C  g  = gravitational acceleration [ft/sec^2]
C  Cv = constant volume heat capacity [ft-lb/(lb R)]
C  Cp = constant pressure heat capacity [ft-lb/(lb R)]
C  J  = convertion factor [ft-lb/Btu]
C  k  = ratio of Cp to Cv
C  Ru = universal gas constant  [ft-lb/(lb R mol)]
C  b  = specific covolume [ft^3/lb]
C-----------------------------------------------------------------
      DOUBLE PRECISION R,MW,g,J,k,Cp,Cv,Ru,b

      PARAMETER(R  = 66.09D0)
      PARAMETER(MW = 23.36D0)
      PARAMETER(g  = 32.2D0)
      PARAMETER(J  = 778.0D0)
      PARAMETER(k  = 1.243D0)
      PARAMETER(Cp = 336.7D0)
      PARAMETER(Cv = 270.698D0)
      PARAMETER(Ru = 1544.0D0)
      PARAMETER(b  = 0.01649D0)
```

==
==

INTENTIONALLY LEFT BLANK.

NO. OF
COPIES   ORGANIZATION

2   ADMINISTRATOR
     ATTN DTIC DDA
     DEFENSE TECHNICAL INFO CTR
     CAMERON STATION
     ALEXANDRIA VA 22304-6145

1   DIRECTOR
     ATTN AMSRL OP SD TA
     US ARMY RESEARCH LAB
     2800 POWDER MILL RD
     ADELPHI MD 20783-1145

3   DIRECTOR
     ATTN AMSRL OP SD TL
     US ARMY RESEARCH LAB
     2800 POWDER MILL RD
     ADELPHI MD 20783-1145

1   DIRECTOR
     ATTN AMSRL OP SD TP
     US ARMY RESEARCH LAB
     2800 POWDER MILL RD
     ADELPHI MD 20783-1145

     ABERDEEN PROVING GROUND

2   DIR USARL
     ATTN AMSRL OP AP L (305)

1   HQDA
ATTN SARD TR MS K KOMINOS
PENTAGON
WASHINGTON DC 20310-0103

1   HQDA
ATTN SARD TR DR R CHAIT
PENTAGON
WASHINGTON DC 20310-0103

1   CHAIRMAN
DOD EXPLOSIVES SAFETY BD
HOFFMAN BLDG 1 RM 856 C
2461 EISENHOWER AVE
ALEXANDRIA VA 22331-0600

1   HQS US ARMY MATERIEL CMD
ATTN AMCICP AD M FISETTE
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1   US ARMY BMDS CMD
ADVANCED TECHLGY CTR
PO BOX 1500
HUNTSVILLE AL 35807-3801

1   OFC OF THE PRODUCT MGR
155MM HOWITZER M109A6 PALADIN
ATTN SFAE AR HIP IP
MR R DE KLEINE
PICATINNY ARSENAL NJ
07806-5000

3   PM AFAS
ATTN SFAE ASM AF E
LTC A ELLIS
T KURIATA
J SHIELDS
PICATINNY ARSENAL NJ
07806-5000

1   PM AFAS
ATTN SFAE ASM AF Q W WARREN
PICATINNY ARSENAL NJ
07806-5000

1   CDR US ARMY ARDEC
PROD BASE MDRNZTN AGENCY
ATTN AMSMC PBM A SIKLOSI
PICATINNY ARSENAL NJ
07806-5000

1   CDR US ARMY ARDEC
PROD BASE MDRNZTN AGENCY
ATTN AMSMC PBM E L LAIBSON
PICATINNY ARSENAL NJ
07806-5000

1   PM PEO ARMAMENTS
TANK MAIN ARMAMENT SYSTEM
ATTN AMCPM TMA
PICATINNY ARSENAL NJ
07806-5000

1   PM PEO ARMAMENTS
TANK MAIN ARMAMENT SYSTEM
ATTN AMCPM TMA 105
PICATINNY ARSENAL NJ
07806-5000

1   PM PEO ARMAMENTS
TANK MAIN ARMAMENT SYSTEM
ATTN AMCPM TMA 120
PICATINNY ARSENAL NJ
07806-5000

1   PM PEO ARMAMENTS
TANK MAIN ARMAMENT SYSTEM
ATTN AMCPM TMA AS H YUEN
PICATINNY ARSENAL NJ
07806-5000

2   CDR US ARMY ARDEC
ATTN SMCAR CCH V
C MANDALA
E FENNELL
PICATINNY ARSENAL NJ
07806-5000

1   CDR US ARMY ARDEC
ATTN SMCAR CCH T
L ROSENDORF
PICATINNY ARSENAL NJ
07806-5000

1   CDR US ARMY ARDEC
ATTN SMCAR CCS
PICATINNY ARSENAL NJ
07806-5000

1   CDR US ARMY ARDEC
ATTN SMCAR AEE J LANNON
PICATINNY ARSENAL NJ
07806-5000

5   COMMANDER
US ARMY ARDEC
ATTN SMCAR AEE WW
M MEZGER
J PINTO
D WIEGAND
P LU
C HU
PICATINNY ARSENAL NJ
07806-5000

10   CDR US ARMY ARDEC
ATTN SMCAR AEE B
D DOWNS
S EINSTEIN
S WESTLEY
S BERNSTEIN
J RUTKOWSKI
B BRODMAN
P O'REILLY
R CIRINCIONE
P HUI
J O'REILLY
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR AES
S KAPLOWITZ
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR FSA T
M SALSBURY
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR HFM
E BARRIERES
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR FSC G FERDINAND
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR FS T GORA
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR FS DH J FENECK
PICATINNY ARSENAL NJ
07806-5000

3   COMMANDER
US ARMY ARDEC
ATTN SMCAR FSS A
R KOPMANN
B MACHEK
L PINDER
PICATINNY ARSENAL NJ
07806-5000

1   COMMANDER
US ARMY ARDEC
ATTN SMCAR FSN N K CHUNG
PICATINNY ARSENAL NJ
07806-5000

2   DIR BENET LABS
ATTN SMCAR CCB RA
G P O'HARA
G A PFLEGL
WATERVLIET NY 12189-4050

1   DIR BENET LABS
ATTN AMSTA AR CCB T
S SOPOK
WATERVLIET NY 12189-4050

1   DIR BENET LABS
ATTN SMCAR CCB S
F HEISER
WATERVLIET NY 12189-4050

2   CDR US ARMY RSRCH OFC
ATTN TECHNICAL LIBRARY
D MANN
PO BOX 12211
RESEARCH TRIANGLE PARK NC
27709-2211

35

NO. OF COPIES	ORGANIZATION	NO. OF COPIES	ORGANIZATION
7	COMMANDER NAVAL SURFACE WARFARE CTR ATTN T C SMITH K RICE S MITCHELL S PETERS J CONSAGA C GOTZMER TECHNICAL LIBRARY INDIAN HEAD MD 20640-5000	1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G33 T DORAN DAHLGREN VA 22448-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE 730 SILVER SPRING MD 20903-5000	1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE E23 TECHNICAL LIBRARY DAHLGREN VA 22448-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE R 13 R BERNECKER SILVER SPRING MD 20903-5000	2	COMMANDER NAVAL AIR WARFARE CTR ATTN CODE 388 C F PRICE T BOGGS CHINA LAKE CA 93555-6001
1	DIRECTOR US ARMY TRAC FT LEE ATTN ATRC L MR CAMERON FORT LEE VA 23801-6140	2	COMMANDER NAVAL AIR WARFARE CTR ATTN CODE 3895 T PARR R DERR CHINA LAKE CA 93555-6001
1	COMMANDER US ARMY BELVOIR RD&E CTR ATTN STRBE WC FT BELVOIR VA 22060-5606	1	COMMANDER NAVAL AIR WARFARE CTR INFORMATION SCIENCE DIV CHINA LAKE CA 93555-6001
1	US ARMY RSCH DEVELOPMENT & STNDRDZTN GROUP UK ATTN DR ROY E RICHENBACH PSC 802 BOX 15 FPO AE 09499-1500	1	COMMANDING OFFICER NAVAL UNDERWATER SYSTEMS CTR ATTN CODE 5B331 TECH LIBRARY NEWPORT RI 02840
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G30 GUNS & MUNITIONS DIV DAHLGREN VA 22448-5000	1	AFOSR NA ATTN J TISHKOFF BOLLING AFB DC 20332-6448
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G32 GUNS SYSTEMS DIV DAHLGREN VA 22448-5000	1	OLAC PL TSTL ATTN D SHIPLETT EDWARDS AFB CA 93523-5000
		3	AL LSCF ATTN J LEVINE L QUINN T EDWARDS EDWARDS AFB CA 93523-5000

2   CPIA JHU
ATTN H J HOFFMAN
T CHRISTIAN
10630 LITTLE PATUXENT PKWY
SUITE 202
COLUMBIA MD 21044-3200

1   CALIFORNIA INST OF TECH
JET PROPULSION LABORATORY
ATTN L STRAND MS 125 224
4800 OAK GROVE DRIVE
PASADENA CA 91109

3   GEORGIA INST OF TCHNLGY
SCHL OF AEROSPACE ENGNRNG
ATTN E PRICE
W C STRAHLE
B T ZINN
ATLANTA GA 30332

1   UNIVERSITY OF MARYLAND
ATTN DR J D ANDERSON
COLLEGE PARK MD 20740

1   MASSACHUSETTS INST OF
TECHNOLOGY
ATTN T TOONG
77 MASSACHUSETTS AVE
CAMBRIDGE MA 02139-4307

1   UNIVERSITY OF ILLINOIS
DEPT OF MECH ENG
ATTN H KRIER
144MEB 1206 W GREEN ST
URBANA IL 61801

1   UNIVERSITY OF MINNESOTA
DEPT OF MECHNCL ENGNRNG
ATTN E FLETCHER
MINNEAPOLIS MN 55455

3   PENNSYLVANIA STATE UNIV
DEPT OF MECHNCL ENGNRNG
ATTN K KUO
C MERKLE
S THYNELL
V YANG
UNIVERSITY PARK PA 16802

1   AFELM THE RAND CORP
ATTN LIBRARY D
1700 MAIN STREET
SANTA MONICA CA 90401-3297

1   ARROW TECHLGY ASSOC INC
ATTN W HATHAWAY
PO BOX 4218
SOUTH BURLINGTON VT 05401-0042

2   AAI CORPORATION
ATTN J FRANKLE
D CLEVELAND
PO BOX 126
HUNT VALLEY MD 21030-0126

8   ALLIANT TECHSYSTEMS INC
ATTN R E TOMPKINS
J KENNEDY
J BODE
C CANDLAND
L OSGOOD
R BURETTA
R BECKER
M SWENSON
600 SECOND ST NE
HOPKINS MN 55343

1   ELI FREEDMAN AND ASSOCIATES
ATTN E FREEDMAN
2411 DIANA RD
BALTIMORE MD 21209-1525

1   GENERAL APPLIED SCIENCES LAB
ATTN J ERDOS
77 RAYNOR AVE
RONKONKAMA NY 11779-6649

1   GENERAL ELECTRIC COMPANY
TACTICAL SYSTEM DEPT
ATTN J MANDZY
100 PLASTICS AVE
PITTSFIELD MA 01201-3698

1   IITRI
ATTN M J KLEIN
10 W 35TH STREET
CHICAGO IL 60616-3799

NO. OF COPIES	ORGANIZATION
4	HERCULES INC ATTN L GIZZI D A WORRELL W J WORRELL C CHANDLER RADFORD ARMY AMMO PLANT RADFORD VA 24141-0299
2	HERCULES INC ATTN WILLIAM B WALKUP THOMAS F FARABAUGH ALLEGHENY BALLISTICS LAB PO BOX 210 ROCKET CENTER WV 26726
1	HERCULES INC ATTN R CARTWRIGHT AEROSPACE 100 HOWARD BLVD KENVILLE NJ 07847
1	HERCULES INC ATTN B M RIGGLEMAN HERCULES PLAZA WILMINGTON DE 19894
1	MARTIN MARIETTA DEFENSE SYSTEMS ATTN GEORGE KEELER RM 2260 100 PLASTICS AVE PITTSFIELD MA 01201
1	MBR RESEARCH INC ATTN DR MOSHE BEN REUVEN 601 EWING ST SUITE C 22 PRINCETON NJ 08540
1	OLIN CORPORATION ATTN F E WOLF BADGER ARMY AMMO PLANT BARABOO WI 53913
3	OLIN ORDNANCE ATTN E J KIRSCHKE A F GONZALEZ D W WORTHINGTON PO BOX 222 ST MARKS FL 32355-0222

NO. OF COPIES	ORGANIZATION
1	OLIN ORDNANCE ATTN H A MCELROY 10101 9TH STREET NORTH ST PETERSBURG FL 33716
1	PAUL GOUGH ASSOC INC ATTN P S GOUGH 1048 SOUTH ST PORTSMOUTH NH 03801-5423
1	PHYSICS INTERNATIONAL LIBRARY ATTN H WAYNE WAMPLER PO BOX 5010 SAN LEANDRO CA 94577-0599
2	PRINCETON CMBSTN RSRCH LABS INC ATTN N A MESSINA N MER PRINCETON CORPORATE PLAZA 11 DEERPARK DR BLDG IV SUITE 119 MONMOUTH JUNCTION NJ 08852
1	TEXTRON DEFENSE SYSTEM ATTN A PATRICK 2385 REVERE BEACH PKWY EVERETT MA 02149-5900
3	ROCKWELL INTRNTNL ATTN BA08 J FLANAGAN J GRAY R B EDELMAN ROCKETDYNE DIV 6633 CANOGA AVE CANOGA PARK CA 91303-2703
2	ROCKWELL INTRNTNL SCIENCE CTR ATTN DR S CHAKRAVARTHY DR S PALANISWAMY 1049 CAMINO DOS RIOS THOUSAND OAKS CA 91360
1	SAIC ATTN M PALMER 2109 AIR PARK RD ALBUQUERQUE NM 87106
1	SOUTHWEST RSRCH INSTITUTE ATTN J P RIEGEL 6220 CULEBRA ROAD SAN ANTONIO TX 78228-0510

NO. OF COPIES	ORGANIZATION	NO. OF COPIES	ORGANIZATION
1	SVERDRUP TECHLGY INC ATTN DR JOHN DEUR 2001 AEROSPACE PARKWAY BROOK PARK OH 44142		ABERDEEN PROVING GROUND
3	THIOKOL CORPORATION ATTN R WILLER R BIDDLE TECH LIBRARY ELKTON DIVISION PO BOX 241 ELKTON MD 21921-0241	1	CDR USA ATC ATTN STECS LI R HENDRICKSEN
1	VERITAY TECHLGY INC ATTN E FISHER 4845 MILLERSPORT HWY EAST AMHERST NY 14501-0305		
1	UNIVERSAL PROPULSION COMPANY ATTN H J MCSPADDEN 25401 NORTH CENTRAL AVE PHOENIX AZ 85027-7837		
1	SRI INTERNATIONAL ATTN TECH LIBRARY PROPULSION SCIENCES DIV 333 RAVENWOOD AVE MENLO PARK CA 94025-3493		

ABERDEEN PROVING GROUND

54   DIR USARL
    ATTN   AMSRL WT P A HORST
           AMSRL WT PA
            T MINOR
            A BIRK
            K WHITE
            L-M CHANG (5 CP)
            J COLBURN
            P CONROY
            G KELLER
            D KOOKER
            M NUSCA
            T ROSENBERGER
            A BRANT
            S HOWARD (5 CP)
            D KRUCZYNSKI
            C RUTH
            I STOBIE
            A WILLIAMS
           AMSRL WT PB
            P PLOSTINS
           AMSRL WT PC
            G ADAMS
            R ANDERSON
            M MILLER
           AMSRL WT T
            W MORRISON
           AMSRL WT TB
            R FREY
           AMSRL WT TC
            W DE ROSSET
            F GRACE
            B SORENSEN
           AMSRL WT TD
            A DIETRICH
            K FRANK
           AMSRL WT WA
            B MOORE
            H ROGERS
            A BARAN
           AMSRL WT WB
            F BRANDON

          AMSRL SC
           W MERMAGEN
          AMSRL SC C
           W STUREK
          AMSRL SC CC
           A CELMINS
           J GROSH (5 CP)
          AMSRL SC I
           M HIRSCHBERG
           R KASTE
          AMSRL SC S
           A MARK
          AMSRL SL
           J SMITH
          AMSRL SL I
           D HASKELL
          AMSRL SL BG
           D KIRK

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ___ARL-TR-1094 (Howard)___ Date of Report ___June 1996___

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

_____

_____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

_____

_____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

_____

_____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

_____

_____

_____

CURRENT
ADDRESS

Organization _____

Name _____

Street or P.O. Box No. _____

City, State, Zip Code _____

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization _____

Name _____

Street or P.O. Box No. _____

City, State, Zip Code _____

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)